



DESCRIPTION: SEVEN PAIR 28 AWG, FOIL, DRAIN, BRAID, BLACK PVC JACKET	
CONDUCTORS:	28 7/36 TINNED COPPER (.015" NOM OD)
INSULATION:	.008" SR PVC (.031" NOM OD)
PAIRS:	TWIST TWO (2) CONDUCTORS TOGETHER 3/4" LEFT HAND LAY (MAX)
CONSTRUCTION:	SEVEN (7) PAIRS CABLED TOGETHER 2 1/2" LEFT HAND LAY (MAX)
TAPE SHIELD	ALUMINUM/POLYESTER/ALUMINUM TAPE SHIELD 25% MINIMUM OVERLAP, 100% COVERAGE
DRAIN WIRE	28 7/36 TINNED COPPER DRAIN WIRE (BETWEEN TAPE SHIELD AND BRAID SHIELD)
BRAID SHIELD	TINNED COPPER BRAID SHIELD, 85% COVERAGE
JACKET:	.053" BLACK PVC
OD:	.287" (.272" ABSOLUTE MIN / .302" ABSOLUTE MAX)
JACKET PRINT IN WHITE INK:	E151405 28 AWG TYPE CM 105C (UL)...AWM 2661...C(UL) TYPE CMG FT-4...105C 300V...CE...ROHS
RATINGS:	UL CM & C(UL) CMG (UL FOR CANADA) 105C 300V UL AWM 2661 105C 300V ROHS COMPLIANT CE COMPLIANT



CABLE TECHNOLOGY, INC.

73 RIVER ROAD - WILLINGTON, CT 06279 - (860) 429 - 7889 FAX (860) 429 - 3615

PART NO:	CT-E1486		
REVISION:	C		PW: 1597
	B: 7/9/2014: CHANGED OD AND TOLERANCE C: 12/23/2014 CHANGED PRINT LEGEND		