



For more Information
please call

1-800-Belden1



General Description:

SCSI, 28 AWG stranded (7x36) TC conductors, non-plenum, flame-retardant polyolefin insulation, polypropylene buffer layer, twisted pairs, overall Beldefoil® shield + TC braid shield (85% coverage), see color code chart (below), light gray PVC jacket.

Usage (Overall)

Suitable Applications: SCSI 2

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	# Pairs	AWG	Stranding	Conductor Material
68	34	28	7x36	TC - Tinned Copper

Total Number of Conductors: 68

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
FRPO - Flame Retardant Polyolefin	0.254

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	85

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.965

Overall Cable

Overall Cabling Separator Material: Foam Polypropylene Binder Tape

Overall Nominal Diameter: 12.192 mm

Pair

Pair Color Code Chart:

Number	Color
1	White/Blue & Blue/White
2	White/Orange & Orange/White
3	White/Green & Green/White
4	White/Brown & Brown/White
5	White/Gray & Gray/White
6	Red/Blue & Blue/Red
7	Red/Orange & Orange/Red
8	Red/Green & Green/Red
9	Red/Brown & Brown/Red
10	Red/Gray & Gray/Red
11	Black/Blue & Blue/Black
12	Black/Orange & Orange/Black
13	Black/Green & Green/Black
14	Black/Brown & Brown/Black
15	Black/Gray & Gray/Black
16	Yellow/Blue & Blue/Yellow
17	Yellow/Orange & Orange/Yellow
18	Yellow/Green & Green/Yellow
19	Yellow/Brown & Brown/Yellow
20	Yellow/Gray & Gray/Yellow

21	Purple/Blue & Blue/Purple
22	Purple/Orange & Orange/Purple
23	Purple/Green & Green/Purple
24	Purple/Brown & Brown/Purple
25	Purple/Gray & Gray/Purple
26	White & Blue
27	White & Orange
28	White & Green
29	White & Brown
30	White & Gray
31	Red & Blue
32	Red & Orange
33	Red & Green
34	Red & Brown

Mechanical Characteristics (Overall)

Bulk Cable Weight:	190.490 Kg/Km
Max. Recommended Pulling Tension:	800.676 N
Min. Bend Radius/Minor Axis:	127 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CL2, CM
CEC/C(UL) Specification:	CM
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/13/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 UL Loading
-----------------------	-------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
----------------------	----

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Description	Impedance (Ohm)	Tolerance (Ohms)
Differential TDR	122.000	+38 -7
Single Ended TDR	84.000	± 12

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
41.6687

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)
98.43

Nominal Velocity of Propagation:

VP (%)
66

Nominal Delay:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Delay (ns/m)
Pair-to-Pair				0.13124

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
212.937

Nominal Outer Shield DC Resistance:

METRIC MEASUREMENT VERSION

1403A Multi-Conductor - Small Computer System Interface

DCR @ 20°C (Ohm/km)

4.9215

Max. Attenuation:

()	Freq. (MHz)	Attenuation (dB/100m)
	7.5463	5.000
		7.546

Max. Operating Voltage - UL:

Voltage

300 V RMS

Max. Recommended Current:

Current

0.5 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1403A F2V1000	1,000 FT	136.000 LB	GRAY, DEC	C	34 PR #28 FRPP SH PVC
1403A F2V500	500 FT	71.500 LB	GRAY, DEC	C	34 PR #28 FRPP SH PVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 03-15-2016

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).