

**Description:** 2/C 16 AWG, Overall TPR Jacket

GENERAL PRODUCT SPECIFICATION Phone 800-316-8877 Fax 978-368-1275 www.jamesmonroewire.com

Create Date: 12/02/2020

JM Part No: TBD

**Reference: 05-0486** 

**Components** Two 16 AWG, SRPVC Insulated Conductors

Nom OD

Conductor: 16 AWG, 19/.0117 bare copper

Insulation: .016" nominal wall of SRPVC (see color code)

.088"

**Overall Cable Construction** 

Cabling: 2 conductors pulled in parallel

Separator: Tissue Tape

Jacket: .036" nominal wall of pressured Black TPR .250" ± .010"

**Print** 

Unprinted

**Color Code** 

1. Black 2. Red

Requirements

Approvals:

Temperature:

105°C

Materials are RoHS 3 Compliant (2011/65/EU & EU 2015/863)

Voltage:

300 V

Cable Weight:

21 lbs/Mft

Copper Weight:

16 lbs/Mft

| Revised By: Revised By: | Written By: | KA/BA | 12/02/2020 | Rev. 0 | Initial Issue |
|-------------------------|-------------|-------|------------|--------|---------------|
| Revised By:             | Revised By: |       |            |        |               |
|                         | Revised By: |       |            |        |               |