

Web site: www.marinco.com

Phone: 800-307-6702

Date: April 2013

Rev: 02

Inlet, Non-metallic
30A, 125V

Catalog Number: 301EL-B

Item: Inlet, non-metallic locking
Rating: 30 amperes, 125 volts
Materials: Cap & Bezel are glass-filled polyester.
Plug body is nylon with CTI greater than 600 volts.
Contact blades and terminal parts are nickel plated brass.
Rear enclosure is glass-filled polyester with UL flammability rating of 94V-0.

Terminals: Clamp-type terminals. No. 10 terminal screws accept up to 8 AWG wire.

Enclosure: Provided. Has integral strain relief for oval jacketed cable.

Blades: Blades are solid brass 0.060" thick.

Mounting Screws: Not provided. No. 8 panhead recommended. Mounting holes are 0.16" diameter on a 2.43" square pattern.

Mounting Gasket: Solid Neoprene, 1/8" thick.

Cap Closure: Pressure close. Provided with Easy Lock™ bayonet style locking system. Provides weather seal when used with cords having threaded, or Easy Lock™, sealing rings.

Listings: UL Marine listed, File E57672
CSA certified, File LR81290
Complies with ABYC and Coast Guard Standards.

Dimensions:

Not to scale
Dimensions in inches

