



Part Number: 31518

Lead Wire, #18 Str TC, Neoprene Ins, AWM 3044 CAS TYPE CL902

[Request Sample](#)

Product Description

Low Temp Rubber Lead Wire, 18AWG (16x30) Tinned Copper, Neoprene Insulation, AWM 3044 CAS TYPE CL902300V 90C

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
18	16x30	TC - Tinned Copper	1

Conductor Count:	1
Conductor Size:	18 AWG

Insulation

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Min. Average Wall Thickness
Neoprene	Neoprene	0.109 in	0.0325 in	0.03 in

Outer Jacket Material

Material	Nominal Diameter
No Jacket	0.109 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
6 Ohm/1000ft

Current

Element	Max. Recommended Current [A]
Single Conductor in Free Air @ 30C Ambient	Single Conductor in Free Air @ 30C Ambient 18 amps

Voltage

UL Description	UL Voltage Rating
UL AWM 3044	300 V RMS

Temperature Range

UL Temp Rating:	90°C Dry, 60°C Oil
Operating Temp Range:	-30°C To +90°C

Mechanical Characteristics

Recommended Max Baking Cycles:	24 Hours @ 300°F (149°C) ~ 8 Hours @ 325°F (163°C) ~ 15 Minutes @ 450°F (232°C)
Bulk Cable Weight:	10 lbs/1000ft

Standards

UL AWM Style:	3044
CSA Rating:	300 V RMS, 90°C

CSA Type:	CL902
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LSOH, Toxicity Testing

UL Flammability:	Horizontal
Other Flammability:	UL Horizontal Flame
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Footnote
31518 0102000	Black	C 1
31518 010500	Black	F
31518 0105000	Black	C I U Z
31518 0062000	Blue, Light	I U
31518 0065000	Blue, Light	C I U Z
31518 0015000	Brown	C I U Z
31518 005500	Green, Dark	F
31518 0055000	Green, Dark	C I U Z
31518 0025000	Red	C I U Z
31518 0095000	White	C I U Z
31518 0045000	Yellow	C I U Z

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	I - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'.
Footnote:	U - TOPCOAT ADDERS ON STOCK SOLID COLORS. MINIMUM ORDER 10,000' PER COLOR COMBINATION. (SEE TOPCOAT ADDER TABLE)
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.
Footnote:	1 - FINAL PUT-UP LENGTH MAY VARY -20% TO +10% FROM LENGTH SHOWN.
Footnote:	F - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'.

Product Notes

Notes:	24 Hours @ 300°F (149°C) ~ 8 Hours @ 325°F (163°C) ~ 15 Minutes @ 450°F (232°C)
--------	---

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.