

TABLE OF CONTENTS

- A. GENERAL INFORMATION
- B. APPLIANCE WIRE
 - 1. Appliance Wire (PVC)
 - Machine Tool Wire, Dual Rated, UL-1015/1230/TEW
 - Lead Wire, UL-1007, UL-1028
 - UL-1056, UL-1060
 - 2. Appliance Lead Wire (XLPE)
 - UL-3173, 3915, 3196
 - UL-3199
 - UL-3237, 3290
 - UL-3321
 - 3. Appliance Lead Wire (Neoprene) NO LONGER AVAILABLE
UL-3039, 3044, 3046
 - 4. Appliance Lead Wire (EPDM) NO LONGER AVAILABLE
UL-3284, 3328, 3340, 3484, 3556
 - 5. Hermetic Lead Wire
 - UL-5170 (DMD)
 - UL-5058 (DTMD)
- C. AUTOMOTIVE WIRE & CABLE
 - 1. Automotive Primary Wire (PVC)
 - GPT (General Purpose Thermoplastic)
 - HDT, HTP (Heavy Duty Thermoplastic)
 - TWP (Thin Wall Thermoplastic)
 - UTP (Ultra-Thin Wall Thermoplastic)
 - 2. Automotive Primary Wire (XLPE)
 - GXL (General Purpose Crosslink)
 - SXL (Special Purpose Crosslink)
 - TXL (Thin Wall Crosslink)
 - UXL (Ultra-Thin Wall Crosslink)
 - 3. Automotive Battery Cable
 - SGT (PVC)
 - SGX (XLPE)
 - STX (Thin Wall XLPE)
- D. MARINE WIRE
 - Marine Wire (PVC)
 - Marine Battery Cable (SGT)
- E. CONSTRUCTION WIRE (XLPE)
 - XHHW, XHHF
 - RHH, USE, RHW
- F. SWITCHGEAR WIRE (XLPE)
 - SIS
 - SIS-F (VW-1 Rating)
- G. MULTI-CONDUCTOR CABLE (PVC Jacket)
 - Trailer Cable
 - Boat Cable



ORDERING INFORMATION

PART NUMBER

GXL - 16 - 19 - B - xx
 Product Type Gauge Stranding Coating Specialty Code

Product Type: Type as referenced on catalog page (GXL, TWP,3321, etc.)
 Gauge: Wire gauge (16, 1/0, etc.)
 Stranding: Number of strands (19, 133, etc.) or special number (1000, 1010, etc.)
 Coating: "B" for bare copper or "T" for tinned copper
 Specialty Code: See customer service for designation

PACKAGING

Reels: Wood, Non-returnable
 12R - 12" Reel
 15B - 15" X 10", 1-9/16" Arbor
 16B - 16" x 12"
 18A - 18" x 14", 2" Arbor
 18B - 18" x 14", 1-9/16" Arbor
 18C - 18" x 14", 2" Arbor, 3/4" Flange
 24R - 24" Reel, 2" Arbor
 30A - 30" x 14", 2" Arbor
 30B - 30" Reel, 1-1/2" Flange

Reels: Wood, Non-returnable
 30R - 30" x 14", 1-9/16" Arbor
 36A - 36" x 12", 2" Arbor
 36B - 36" x 14", 3" Arbor

Drums: Fiber, Non-returnable
 35D - 35 Gallon, 20" high x 23" diameter
 55D - 55 Gallon, 30" high x 23" diameter
 75D - 75 Gallon, 42" high x 23" diameter

ACCEPTANCE OF ORDERS:

All orders are subject to written acceptance by Therm-O-Link, Inc. / Vulkor, Inc.

CREDIT:

All orders are subject to credit approval.

PRICING:

Material will be invoiced at the price in effect at the time of shipment.

TERMS OF PAYMENT:

Net 30 days cash.

FREIGHT TERMS:

Prices are FOB factory, shipped collect, unless otherwise stated.

QUANTITY VARIATION:

The quantity shipped against any item on an order is subject to a variation of +/- 10%.

WARRANTY:

Therm-O-Link, Inc. / Vulkor, Inc. warrants that the wire furnished is free from defects in material and workmanship. There is no other warranty expressed or implied.

RETURN POLICY:

No material will be accepted for return without prior written authorization.

APPLIANCE LEAD WIRE

LEAD WIRE

Crosslink polyethylene (XLPE) insulated wire manufactured to UL and CSA standards.

APPLICATIONS:

Internal wiring of appliances.

UL-3173,3195,3196 Tinned Copper 125°C 600 Volts

| Product | #CU/MFT | Stranding | Wall Thickness | Min Order |
|---------------|---------|-----------|----------------|-----------|
| 3173-20-10-T | 3.09 | 10/30 | 2/64 | 100M |
| 3173-18-16-T | 4.94 | 16/30 | 2/64 | 50M |
| 3173-16-26-T | 8.03 | 26/30 | 2/64 | 25M |
| 3173-14-41-T | 12.66 | 41/30 | 2/64 | 25M |
| 3173-12-65-T | 20.80 | 65/30 | 2/64 | 75M |
| 3173-10-105-T | 32.50 | 105/30 | 2/64 | 25M |
| 3195-8-133-T | 53.10 | 133/29 | 3/64 | 25M |
| 3196-6-133-T | 82.20 | 133/27 | 4/64 | 25M |
| 3196-4-133-T | 130.00 | 133/25 | 4/64 | 25M |

UL-3173 7 Strand Tinned Copper 125°C 600 Volts

| Product | #CU/MFT | Stranding | Wall Thickness | Min Order |
|-------------|---------|-----------|----------------|-----------|
| 3173-22-7-T | 2.16 | 7/0102 | 2/64 | 100M |
| 3173-18-7-T | 5.04 | 7/0152 | 2/64 | 100M |
| 3173-16-7-T | 8.00 | 7/0192 | 2/64 | 100M |
| 3173-14-7-T | 12.76 | 7/0242 | 2/64 | 100M |
| 3173-12-7-T | 20.20 | 7/0305 | 2/64 | 100M |
| 3173-10-7-T | 31.72 | 7/0385 | 2/64 | 100M |

Minimum order requirement reflects quantity per color, per release.

800-776-9223 (Ohio) 800-684-7823 (Texas)