

APPLIANCE LEAD WIRE

LEAD WIRE

Crosslink polyethylene (XLPE) insulated wire manufactured to UL and CSA standards.

APPLICATIONS:

Internal wiring of appliances.

UL-3173,3195,3196 Tinned Copper 125°C 600 Volts

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
3173-20-10-T	3.09	10/30	2/64	100M
3173-18-16-T	4.94	16/30	2/64	50M
3173-16-26-T	8.03	26/30	2/64	25M
3173-14-41-T	12.66	41/30	2/64	25M
3173-12-65-T	20.80	65/30	2/64	75M
3173-10-105-T	32.50	105/30	2/64	25M
3195-8-133-T	53.10	133/29	3/64	25M
3196-6-133-T	82.20	133/27	4/64	25M
3196-4-133-T	130.00	133/25	4/64	25M

UL-3173 7 Strand Tinned Copper 125°C 600 Volts

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
3173-22-7-T	2.16	7/0102	2/64	100M
3173-18-7-T	5.04	7/0152	2/64	100M
3173-16-7-T	8.00	7/0192	2/64	100M
3173-14-7-T	12.76	7/0242	2/64	100M
3173-12-7-T	20.20	7/0305	2/64	100M
3173-10-7-T	31.72	7/0385	2/64	100M

Minimum order requirement reflects quantity per color, per release.

800-776-9223 (Ohio) 800-684-7823 (Texas)