

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: 3173-20-10-T
Spec Revision Level: A13
Customer Part Number: 3173/20T10-0

Description: 20 GA AWM 3173 125 DEGC 600V
10 STRANDS TINNED COPPER

Conductor (Stranding): 10 x 30 Awg Tinned Copper ,UL
Conductor OD (Nom) 0.038 inches
Max. Lay Length: 1.0 inch Lay
Min Avg Wall Thickness: 0.030 inches
Min O. D: 0.099 inches
Nom. O. D: 0.102 inches
Max Runout: 0.008 inches
Strip Force: 1" Strippable
Circular Mils (CMA): 989 (Min)
Surface Print: 20 AWG RU AWM STYLE 3173 XLPE 125C 600V
E73051 CSA CL1251 XLPE 125C 600V OR AWM I A/B
125C 600V FT2 LL46012

This Product is RoHS Compliant.

Specification Reference Data

SAE: N/A	Ford: N/A	Chrysler: N/A
UL : AWM 3173/ STD 758	CSA: C22.2 #127-2009	Packard: N/A
Other: N/A		

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Product Engineering Manager)

Date: 5-30-2019