

**Description:** Eight 18 AWG Insulated Conductors  
 Overall Foil Shield and TPE Jacket

**Date:** 9/3/2015

**JM Part Number:** TBD  
**Reference:**

**Component** Eight 18 AWG Insulated Conductors

Conductor: 18 AWG, 19/30 tinned copper

Insulation: .016" nominal wall of PVC (see color code)

Jacket: .005" nominal wall of Clear Nylon .090"

**Cable Construction**

Cabling: Eight conductors cabled together with FR PP Fillers as needed

Drain Wire: 20 AWG, 10/30 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side IN

Separator: Tissue Tape

Jacket: .072" nominal wall of Black TPE .447"

**Color Code**

1. Red	2. Green	3. Black	4. White
5. Yellow	6. Brown	7. Blue	8. Orange

**Print**

**E66440 8/C 18 AWG 9\ AWM 20626 90C 600V ---**  
**LL41103 CSA AWM I/II A/B 90C 600V FT4 ---**  
**CE ROHS + Sequential Footage Markings**

**Requirements**

Temperature: 90°C  
 Voltage: 600V

Approvals: UL AWM Style 20626  
 CSA AWM, FT4  
 CE-LVD and RoHS Complaint (2011/65/EU)

Written By:	RL	9/3/2015	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				