



For more Information  
please call

1-800-Belden1



### General Description:

BOOT 7MM KIT FOR FIELD RJ45 PLUG, BLACK (100-PACK)

### Usage (Overall)

**Related Parts:** Field Plug Kits C5PFCF, C6PFCU, CAPFCF & CAPFCU. Cable 7MM OD.

### Physical Characteristics (Connectivity)

#### Dimensions

Dimensions:

Height (mm)	Width (mm)	Length (mm)
15.748	13.462	25.908

#### Materials

Materials:

Description	Type	Material
Boot	RJ45	PVC

#### Color

**Color:** Black

#### Weight

**Weight:** 0.184 kg

#### Packaging

**Packaging:** Kit of 100 units per Bag.

### Mechanical Characteristics (Connectivity)

**Operating Temperature Range:** -40°C To +85°C

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

**UL Rating:** 94V-0

**EU Directive 2002/95/EC (RoHS):** Yes

**EU RoHS Compliance Date (mm/dd/yyyy):** 07/01/2006

#### Suitability

**Suitability - Indoor:** Yes - Indoor

### Transmission Characteristics (Connectivity)

### Notes (Overall)

**Notes:** For additional information about this product, visit our web at <http://www.belden.com>

**Notes (Cont'd.):** Features: Snagless Tab

### Product Family

Part Number List:

Description	Part Number
8MOD (RJ45) FIELD CRIMPED PLUG KIT CAT5E SHIELDED (25-PACK)	C5PFCF-B25
8MOD (RJ45) FIELD CRIMPED PLUG KIT CAT5E/6 UTP (25-PACK)	C6PFCU-B25
8MOD (RJ45) FIELD CRIMPED PLUG KIT CAT6/6A UTP (25-PACK)	CAPFCU-B25
8MOD (RJ45) FIELD CRIMPED PLUG KIT CAT6/6A SHIELDED (25-PACK)	CAPFCF-B25
BOOT 6MM FOR FIELD CRIMPED PLUG, BLACK (100-PACK)	CB6MMBK-B100
BOOT 7MM FOR FIELD CRIMPED PLUG, BLACK (100-PACK)	CB7MMBK-B100

## METRIC MEASUREMENT VERSION

## CB7MMBK-B100 Modular Connectors - BOOT 7MM KIT

BOOT 8MM FOR FIELD CRIMPED PLUG, BLACK (100-PACK)	CB8MMBK-B100
CRIMPING TOOL FOR FIELD RJ45 PLUG	CTPFC01

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
CB7MMBK-B100	1 EA	0.000 KG			BOOT 7 MM FOR FIELD CRIMPED

Revision Number: 0    Revision Date: 01-30-2015

© 2015 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.