



Hueson P/N #C5580

Issue Date: 9/4/2015

Issue: 1

**Construction**

<b>Description:</b>	<b>18/C 18 AWG PVC/PUR HPI Lutze Eq</b>	<b>Diam. (In)</b>
<b>Component:</b>	18 Conductors	
<b>Conductor:</b>	18 AWG 41/34 Bare Copper to ASTM B-174	0.047"
<b>Insulation:</b>	0.012" PVC Insulation	0.071"
<b>Color Code:</b>	White, Black, Red, Brown, Violet, Wht/Blk, Wht/Red, Wht/Grn, Wht/Org, Wht/Blu, Wht/Yel, Wht/Brn, Wht/Vio, Blk/Yel	0.071"
<b>Cable Assembly:</b>	18 Conductors Cabled (1f + 6/C + 12/C)	0.355"
<b>Fillers</b>	Fibrillated polypropylene or solid center filler for roundness	0.355"
<b>Tape:</b>	Non-Woven or Tissue Separator Tape for Strip-Ability	0.358"
<b>Jacket:</b>	0.035" Polyurethane	0.428"
<b>Jacket Color:</b>	Gray	0.428"

Print:

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>	<u>UL List</u>
<b>UL</b>	AWM-20233	80°C	300	FT-2	
Canadian cRU	AWM	80°C	300	FT-2	

**Environmental Compliance**

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65:

**Drawing/Rotation:**

