

**1. CONDUCTOR:**

- 1.1 Size and Material: 18 19/30 AWG nickel-plated copper wire.
- 1.2 O.D.: .047" nom.

**2. INSULATION:**

- 2.1 Extruded PTFE.
- 2.2 O.D.: .101" nom.
- 2.3 Marking on the insulation: not required as per UL standards.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 25 KVDC
- 3.2 Temperature rating: 250°C
- 3.3 Flame rating: VW-1 / Horizontal flame


**4. REFERENCES:**

- 4.1 UL Subject 758 (AWM), Style 1911.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>Daniel Curson</i>		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com		
						Date: February 20, 2020						
						Verified: <i>Daniel Curson</i>		Description: <b>XE27N1819/30-X</b>				
						Date: February 20, 2020						
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.								Size: <b>A</b>	Scale: ---	Page: 1 of 1	Code Ident. No: <b>57104</b>	Specification No.: <b>F00847-X</b>