

N7599-HGG

Ground Fault Circuit Interrupter (GFCI)



UPC Code: 07847760178

Country of Origin: China

Brand Features

Testing a GFCI is a good idea that's sometimes forgotten. Now the SmartlockPro Self-Test GFCI automates the process and performs a self-test every fifteen minutes. It adds an extra level of safety, testing itself to confirm that protected power is available. If the self-test detects any condition that would indicate GFCI protection might be compromised, visual and audible indicators provide an alert. All these robust features are packed into the slimmest GFCI profile on the market for easier installation in residential and commercial settings.

Item Description

15 Amp, 125 Volt Receptacle, Hospital Grade, 20 Amp Feed-Through, SmartLock Pro Slim GFCI, monochromatic, back and side wired, wallplate and self grounding clip included - Grey

Technical Information

AC Horsepower Ratings

At Rated Voltage: 1 HP

Electrical Specifications

Amperage: 15 Amp

Voltage: 125 Volt

NEMA: 5-15R

Pole: 2

Wire: 3

Frequency (Hertz): 60

Short Circuit Current Rating: 10kA

Feed-Through Current: 20 Amp

Environmental Specifications

Flammability: Rated V-0 per UL94

Operating Temperature: -35C to +66C

Material Specifications

Face Material: PBT

Body Material: Polycarbonate

Terminal Screws: Plated Steel

Grounding Screw: Plated Steel

Clamps: Brass

Strap Material: Galvanized Steel

Mechanical Specifications

Terminal Accom.: 14-10 AWG

Product ID: Ratings permanently marked on device

Performance Data

Trip Level: Class A, 5mA plus or minus 1mA

Diagnostics: LED

Product Features

Color: Grey

Standards and Certifications

NEMA: WD-1 & WD-6

ANSI: C-73

UL 498: File E13399

CSA C22.2 No. 42: File LR-57811

NOM: 057

UL 943: File E48380

UL Fed Spec WC-596: Yes

Warranty

Warranty: 2 Year Limited

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 ·

FAX: 1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2012-2016 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

