

Specification Issue Date:

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

1//1 & 22/13 TYI /DVC CARLE

| tem Descr | iption: | 14/1 & Z | 2/13 IXL/ | PVC CAB | LE | | | | | | | |
|--------------------------|---|------------------|----------------------------------|-----------------|---------------------|----------------|-------------------|--|---|--------------|---------------|--------------|
| Construction Parameters: | | | | | | | | | Diameter | | | |
| Component 1: | | | | | | | | | 0.103 | | | |
| Conductor: | 14 AWG 41/.0099 Ba | re Copper | | | | | | | | | | |
| nsulation: | XLPE-Halogen Free | Nom Wall: | 0.017 | | | | | | | | | |
| Color Code: | Black | | | | | | | | | | | |
| Component 2: | | | | | | | | | 0.062 | | | |
| Conductor: | 22 AWG 7/30 Bare C | opper | | | | | | | | | | |
| nsulation: | XLPE-Halogen Free | Nom Wall: | 0.016 | | | | | | | | | |
| Color Code: | Lt Blue Lt Blue/White | Pink Green/ | White Gree | n Red Red/W | hite Orange | Yellow White | e Brown Vio | let Brown/Whi | ite | | | |
| Cabling: | | | | | | | | | | | | |
| ay Length: | 3.75 | | | | | | | | | | | |
| acketing: | | | | | | | | | | | | |
| Outer Jacket: | PVC | Nom Wall: | 0.035 | | | | | | 0.345 | | | |
| acket Color: | BLACK | | | | | | | | | | | |
| egend Type: egend: | InkJet 22 AWG 13/C + 14 A REQUIREMENTS OF | | | | | | | | | VC -MEETS | THE | |
| Sequential Marki | | Continuous | 1 O V/OOIVEIN | om Redion | | W// NDE 114 00 | / | // // // // // // // // // // // // // | , | | | |
| Physical Pro | perties: | | | | | | | | | | | |
| emperature Rang | ge: | 125°C Condu | uctors/105°C | Jacket | | | | | | | | |
| Electrical Pro | perties: | | | | | | | | | | | |
| oltage Rating: | | 300V RMS | | | | | | | | | | |
| ndustry App | rovals: | | | | Features: | | | | Compliance: | | | |
| lone | | | | | Sunlight Resistant: | | UV Sun Res | | RoHS: Complies with EU Dir. 2011/65/EU (RoHS-2) | | | |
| Component | No. | No. | Nom. Cond. Insulation Wall, Nom. | | | Jacket 1 | Jacket Wall, Nom. | | O.D., Nom. | | Net Weight | |
| Number | Cond. | Gauge AWG/MCM | Strands | DCR Ω/M' | Inches | mm | Inches | mm | Inches | mm | Lb./kft. | kg/km |
| Component 1 | 1 | 14 | 41/.0099 | 2.64 | 0.017 | 0.42 | 0.035 | 0.89 | 0.345 | 8.76 | 64 | 94 |
| Component 2 | 13 | 22 | 7/.0096 | 15.26 | 0.016 | 0.41 | | | | | | |
| lote: All dimen | sions & weights are i | nominal subje | ect to indust | ry standards a | and tolerance | es unless ot | herwise not | ed. | | | | |
| | U Dir. 2011/65/EU (Rol Il accept all factory lenç | | percent of to | otal order requ | ested. | | | | | | | |
| urposes only ar | presented here is, to the nd does not create a bi Southwire's standard to ation contained herein | nding obligation | n or liability o | on Southwire or | confer any ri | ghts on any o | customer. Th | e sale of produ | ucts(s) is condi | itioned upon | acceptance of | f a purchase |
| his specification | n is proprietary intellect | ual property of | Southwire. | Any information | n contained h | erein shall no | t be disclose | d to any party | without written | consent of S | Southwire. | |
| Customer Company Name: | | | | | | | | Date: | | | | |
| Customer Approval: | | | | | | | | Customer Ti | tle: | | | _ |
| pecification Issue Date: | | 10/2/2015 | | Rev Level: | 1 | | ERF#: | 331601 | Designed By: PEM | | | PEM |