

TABLE OF CONTENTS

- A. GENERAL INFORMATION
- B. APPLIANCE WIRE
 - 1. Appliance Wire (PVC)
 - Machine Tool Wire, Dual Rated, UL-1015/1230/TEW
 - Lead Wire, UL-1007, UL-1028
 - UL-1056, UL-1060
 - 2. Appliance Lead Wire (XLPE)
 - UL-3173, 3915, 3196
 - UL-3199
 - UL-3237, 3290
 - UL-3321
 - 3. Appliance Lead Wire (Neoprene) NO LONGER AVAILABLE
UL-3039, 3044, 3046
 - 4. Appliance Lead Wire (EPDM) NO LONGER AVAILABLE
UL-3284, 3328, 3340, 3484, 3556
 - 5. Hermetic Lead Wire
 - UL-5170 (DMD)
 - UL-5058 (DTMD)
- C. AUTOMOTIVE WIRE & CABLE
 - 1. Automotive Primary Wire (PVC)
 - GPT (General Purpose Thermoplastic)
 - HDT, HTP (Heavy Duty Thermoplastic)
 - TWP (Thin Wall Thermoplastic)
 - UTP (Ultra-Thin Wall Thermoplastic)
 - 2. Automotive Primary Wire (XLPE)
 - GXL (General Purpose Crosslink)
 - SXL (Special Purpose Crosslink)
 - TXL (Thin Wall Crosslink)
 - UXL (Ultra-Thin Wall Crosslink)
 - 3. Automotive Battery Cable
 - SGT (PVC)
 - SGX (XLPE)
 - STX (Thin Wall XLPE)
- D. MARINE WIRE
 - Marine Wire (PVC)
 - Marine Battery Cable (SGT)
- E. CONSTRUCTION WIRE (XLPE)
 - XHHW, XHHF
 - RHH, USE, RHW
- F. SWITCHGEAR WIRE (XLPE)
 - SIS
 - SIS-F (VW-1 Rating)
- G. MULTI-CONDUCTOR CABLE (PVC Jacket)
 - Trailer Cable
 - Boat Cable



ORDERING INFORMATION

PART NUMBER

GXL - 16 - 19 - B - xx
 Product Type Gauge Stranding Coating Specialty Code

Product Type: Type as referenced on catalog page (GXL, TWP,3321, etc.)
 Gauge: Wire gauge (16, 1/0, etc.)
 Stranding: Number of strands (19, 133, etc.) or special number (1000, 1010, etc.)
 Coating: "B" for bare copper or "T" for tinned copper
 Specialty Code: See customer service for designation

PACKAGING

Reels: Wood, Non-returnable
 12R - 12" Reel
 15B - 15" X 10", 1-9/16" Arbor
 16B - 16" x 12"
 18A - 18" x 14", 2" Arbor
 18B - 18" x 14", 1-9/16" Arbor
 18C - 18" x 14", 2" Arbor, 3/4" Flange
 24R - 24" Reel, 2" Arbor
 30A - 30" x 14", 2" Arbor
 30B - 30" Reel, 1-1/2" Flange

Reels: Wood, Non-returnable
 30R - 30" x 14", 1-9/16" Arbor
 36A - 36" x 12", 2" Arbor
 36B - 36" x 14", 3" Arbor

Drums: Fiber, Non-returnable
 35D - 35 Gallon, 20" high x 23" diameter
 55D - 55 Gallon, 30" high x 23" diameter
 75D - 75 Gallon, 42" high x 23" diameter

ACCEPTANCE OF ORDERS:

All orders are subject to written acceptance by Therm-O-Link, Inc. / Vulkor, Inc.

CREDIT:

All orders are subject to credit approval.

PRICING:

Material will be invoiced at the price in effect at the time of shipment.

TERMS OF PAYMENT:

Net 30 days cash.

FREIGHT TERMS:

Prices are FOB factory, shipped collect, unless otherwise stated.

QUANTITY VARIATION:

The quantity shipped against any item on an order is subject to a variation of +/- 10%.

WARRANTY:

Therm-O-Link, Inc. / Vulkor, Inc. warrants that the wire furnished is free from defects in material and workmanship. There is no other warranty expressed or implied.

RETURN POLICY:

No material will be accepted for return without prior written authorization.

APPLIANCE LEAD WIRE

LEAD WIRE

Crosslink polyethylene (XLPE) insulated wire, manufactured to UL and CSA standards.

APPLICATIONS:

Internal wiring of appliances, lighting fixtures and ballasts, and as motor lead wire.

UL-3321 Tinned Copper 150°C 600 Volts				
Product	#CU/MFT	Stranding	Wall Thickness	Min Order
3321-20-10-T	3.09	10/30	2/64	100M
3321-18-16-T	4.94	16/30	2/64	40M
3321-18-7-T	4.50	7/0152	2/64	80M
3321-16-26-T	8.03	26/30	2/64	25M
3321-16-7-T	8.00	7/0192	2/64	75M
3321-14-19-T	12.70	19/0147	2/64	50M
3321-14-41-T	12.66	41/30	2/64	25M
3321-14-7-T	12.76	7/0242	2/64	50M
3321-12-65-T	20.80	65/30	2/64	25M
3321-12-19-T	20.80	19/0185	2/64	50M
3321-10-105-T	32.50	105/30	2/64	25M

Minimum order requirement reflects quantity per color, per release.

800-776-9223 (Ohio) 800-684-7823 (Texas)