

20 & 30 Amp Wetguard Locking Devices

20A: 4-Pole, 4-Wire • 4-Pole, 5-Wire — 30A: 2-Pole, 3-Wire • 3-Pole, 3-Wire

**LIFETIME
WARRANTY**

Amp	Volt	NEMA Configuration		Plug	Plug Cap	Connector	Connector Cap	Single Outlet	Duplex Outlet	Single Inlet	Connector for Single Inlet	Single Receptacle	Receptacle Cover with Gasket
Locking 4-Pole, 4-Wire Devices													
20	3ØY 120/208	Non-NEMA		26W09	26W*	27W09	50W52*	97W09-S	---	66W09	76W09-C	7410-B	60W04*
Locking 4-Pole, 5-Wire Devices													
20	3ØY 120/208	L21-20		26W81*	26W*	27W81*	50W52*	97W81-S	---	66W81	76W81-C	2510	60W04*
20	3ØY 277/480	L22-20		26W82	26W*	27W82	50W52*	97W82-S	---	66W82	76W82-C	2520	60W04*
20	3ØY 347/600	L23-20		26W83	26W*	27W83	50W52*	97W83-S	---	66W83	76W83-C	2530	60W04*
20	250	Non-NEMA		26W10	26W*	27W10	50W52*	97W10-S	---	66W10	76W10-C	---	60W04*
10	600												
Locking 2-Pole, 3-Wire Devices													
30	125	L5-30		28W47*	28W*	29W47*	50W54*	99W47-S	---	68W47	78W47-C	26CM-10	60W05*
30	250	L6-30		28W48	28W*	29W48	50W54*	99W48-S	---	68W48	78W48-C	26CM-20	60W05*
30	277	L7-30		28W49	28W*	29W49	50W54*	99W49-S	---	68W49	78W49-C	2630	60W05*
Locking 3-Pole, 3-Wire Devices													
30	125/250	Non-NEMA		28W08	28W*	29W08	50W54*	99W08-S	---	68W08	78W08-C	3330	60W05*

NEMA configuration diagrams represent plug blade configuration.

*Available in black. To order, add "-B" suffix to catalog number.