



Issue Date: 10/22/2015

Construction

Schmitt CBL112451

Issue: 1

Description:	11/C 24(7) TC PVC/PUR Composite	Diam. (In)
Component:	11 Conductors	
Conductor:	24 AWG 7/32 Tinned Copper to ASTM B-8	0.024"
Insulation:	0.01" Semi-Rigid PVC	0.044"
Color Code:	Orange, Brown (Twisted and shielded with 24(7) TC Drain. Foil + Drain In) Black, Red, Green, Yellow, Blue, Violet, Gray, Pink, White	0.044"
Cable Assembly:	9 Conductors Cabled Around the Shielded Twisted Pair (3.0" Left Hand Lay)	0.172"
Fillers	Fibrillated polypropyle as required for roundness (optional)	0.172"
Shield:	Aluminum Mylar Foil Shield (Under Braid Foil Out)	0.174"
Braid:	Tinned Copper Braid Shield 8E #36 7.5 PPI 85% Coverage	0.195"
Tape	Tissue Separator Tape Between Braid and PUR Jacket (optional)	0.198"
Jacket:	0.030" Polyurethane Estane 58202	0.256" Max
Jacket Color:	Matte Black	0.256" Max
Print:	SCHMITT INDUSTRIES -www.schmitt-ind.com	

Environmental Compliance

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65:

Drawing/Rotation:

