



Aerospace Part#: TBD CONTROL CABLE

DESCRIPTION

2 Conductors AWG 22/7x30 TC Overall Foil Shield FEP/FEP Gray

PHYSICAL PROPERTIES

Conductors					
# Conductors	AWG	Material	Material	Wall	Finished OD
2	22/7x30	Tinned Copper	FEP	.018"	.066"

Outer Shield Material Drain Wire

Layer 1 Type	Material	Coverage	Fold Technique	AWG	Material
Overall Foil Shield	Alum / Mylar	100%		24/7x32	Tinned Copper

Outer Jacket Material Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Gray	.015"	.166" Nom.	2" Lay on Cable

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius	
Rated -80C to 150C	18.49 lbs / m	10 X OD	

ELECTRICAL PROPERTIES

Max. Operating Voltage	
Rated 300 Volt	

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Otandards & Environmental Frograms			
Reach / RoHS Compliant	YES		
Suitability	Indoor, Direct Burial, Wet Location		
Resistance	Oil, Gas, Sunlight, Abrasian, Acid		

MISCELLANEOUS

Color Black / White Code:

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

 $[\]ensuremath{^{\star}}$ Specification subject to error $% \left(1\right) =\left(1\right) \left(1\right) \left($