

Part Number: 92769A

Revision: 7/25/2018

**3C 22AWG PVC, UNSH, PVC**
**SOUND, ALARM AND SECURITY**
**A. CONSTRUCTION**

Conductor:	#22 AWG (7/30) Bare Copper	.029" Nom
Insulation:	.008" Wall, Plenum PVC	.045" Nom
Cable Assembly:	3C at 4.00" LHL	.097" Nom
Jacket:	.015" Wall, Plenum PVC	.127" ± .006"
Ripcord:	Plenum Ripcord	
Jacket Color:	White	
Print Legend:	<b>CAROL(R) 22 AWG -- 92769A -- 75C E60233-8 (UL) CL3P -- C(UL)US CMP -- CE ROHS-2 -- MADE IN USA (date code - MM/YY) (sequential footage)</b>	
Sequential Footage:	Yes.	

**DIAMETERS**
**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 13	Type CL3P
National Electrical Code	Article 800
UL Standard 444	Type CMP
EU Directive 2006/95/EC (LVD)	CE Compliant
EU Directive 2002/95/EC (RoHS)	RoHS Compliant
EU Directive 2003/11/EC (BFR)	Compliant
EU Directive 2011/65/EC (RoHS-2)	RoHS-2 Compliant

**C. ELECTRICAL PROPERTIES**

Recommended Temperature:	0°C to +75°C (Installation)
UL Rated Temperature:	-20°C to +75°C (Static Application)
Suggested Working Voltage:	300 Vrms (Max)
Conductor DCR:	16.9 Ohms/1000ft @ 20°C (Max)
Mutual Capacitance:	28.8 pF/ft @ 1kHz (Nom)

**D. COLOR CODE**

COND	COLOR
1	BLACK
2	WHITE
3	RED

**E. CUSTOMER APPROVAL**

Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_