Cable Specification

Component 1	7 PAIR
Conductor:	28 (7/36) AWG TC
Insulation:	0.010" Wall, Nom. PE
Color Code:	14 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED
Pair:	2/Cond Cabled Together
Final Assembly	7 Components
Shield:	AM Foil Tape, 25% Overlap, Min.
Drain Wire:	28 (7/36) AWG TC
Braid:	TC,90% Coverage, Min.
Jacket:	0.035" Wall, Nom., PVC
Jacket OD:	0.269"
Jacket Color:	SLATE

Approvals

UL:	AWM/STYLE 2960
	CL2
	VW-1
CSA:	CMH
	FT1
MIL:	NONE
CE Compliant:	YES
ROHS Compliant:	YES
REACH Compliant:	YES

Miscellaneous

Temperature:	75 C
Voltage:	300 V_{RMS}
Put Ups:	1000 FT PUTUP
Requested Quantity:	1000Ft., 3000Ft.

Application Notes

1 Black
2 Red
3 White
4 Green
5 Orange
6 Blue
7 Brown
8 Yellow
9 Violet
10 Slate
11 Pink
12 Tan
13 Aqua
14 Light Green

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS