



Description: Seven Conductor, 24 AWG,
 O/A Overall Foil Shield,
 PVC Jacket

Date: 11/20/2015

JM Part Number: TBD
Reference: TBD

Components Seven 24 AWG Insulated Conductors

Conductor: 24 AWG, 7/32 tinned copper

Insulation: .010" nominal wall of SR-PVC (see color code) .044"

Cable Construction

Cabling: Seven conductors cabled together

Drain Wire: 24 AWG, 7/32 tinned copper

Foil Shield: Mylar-Aluminum tape, Aluminum side IN

Jacket: .035" nominal wall of Black PVC .205"

Print (White Inkjet)

E66440 7/C 24 AWG SHIELDED AWM 2517 105C 300V --- LL41103
CSA AWM I/II A/B 105C 300V FT1 --- CE

Color Code

- | | |
|---------|----------|
| 1.Black | 5.Brown |
| 2.White | 6.Blue |
| 3.Green | 7.Violet |
| 4.Red | |

Requirements

Temperature: 105C
 Voltage: 300V

Approvals: UL AWM Style 2517
 CSA AWM, FT1
 CE-LVD and RoHS Complaint
 (2011/65/EU)

Written By:	rac	11/20/2015	Rev. 0	Initial
Revised By:				
Revised By:				
Revised By:				

