



Issue Date: 12/29/2015

**Construction**

Issue: 2

<b>Description:</b>		<b>4/Pr 24(7) PP/MPPE OABS</b>						<b>Diam. (In)</b>
<b>Component:</b>	8 Conductors (4 Pair)							
<b>Conductor:</b>	24 AWG 7/32 Tinned Copper to ASTM B-8						0.024"	
<b>Insulation:</b>	0.016" Polypropylene Halogen free						0.056"	
<b>Color Code:</b>	Black, Brown, Red, Orange, Yellow, Green, Blue, White						0.056"	
<b>Cable Assembly:</b>	Twist 4 Twisted pairs 1-1/2" LHL						0.095"	
<b>Pair</b>	<b>Pair 1</b>	Blk + Brn	<b>Pair 2</b>	Red + Org	<b>Pair 3</b>	Yel + Grn	<b>Pair 4</b>	Blu + Wht
<b>Cable Assembly:</b>	Bunch Cable the 4 Twisted Pairs 4-3/4" LHL						0.225"	
<b>Fillers</b>	Fibrillated polypropylene fillers for roundness (optional)						0.225"	
<b>Drain Wire:</b>	No Drain						0.225"	
<b>Tape:</b>	Clear Mylar Tape 25% Minimum Overlap						0.230"	
<b>Braid:</b>	Tinned Copper Braid Shield 90% Coverage 36 AWG						0.250"	
<b>Jacket:</b>	0.045" Low Smoke Halogen Free						0.350"	
<b>Jacket Color:</b>	Black						0.350"	

Print: **Printed: # 3A59241H01**  
 Once every meter

Specifications: **Flame**  
 VW-1

- Environmental Compliance**
- EU Directive 2011/65/EC(RoHS):
  - REACH Regulation (EC 1907/2006):
  - California Prop 65: