



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: sales@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

6-Jan-2016

Product Number : 6062003TUV.1

RoHS

Trailer Cable 3/C 20/19 AWG Stranded Tinned Copper
XLPE Insulation
PVC Jacket

General Specification of Product :

Final Diameter :	0.237 inches	6.020 mm
Total Cable Weight:	54 kg/km	36 lbs/1000 ft
Conductor :	20 AWG 19 Stranded Tinned Copper Conductor	
Insulation :	XLPE	
Ripcord :	NO RIPCORDER	
Outer Jacket :	PVC	

Print Notes :

Standard Print : TRAILER CABLE -65°C/-85°F 3/C 20 AWG RoHS

Electrical Characteristics :

DC Resistance 25°C:	10.6 Ohms / 1000 ft
Mutual Capacitance :	20.3 pF/ft
Impedance :	100 Ohms
Velocity of Prop :	65 %
Inductance. :	1.2 mH/km
Ampacity 30°C :	9.5 Amps

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 30 years.

(All of the above values are approximated to within +/- 10%)

6062003TUV.1