



Specification Sheet

Lake Cable Part #: FF203T41-NUL

Description: 20 AWG 3 conductors 41 strands tinned copper wire with FEP insulation, unshielded, with an overall FEP jacket for low-voltage electronic cable applications

- 1. Conductor**
 - 1.1.AWG Size & Stranding: 20 AWG 41 Strands
 - 1.2.Material: Annealed Tinned Copper
 - 1.3.Conductor Count: 3 Conductors
- 2. Insulation**
 - 2.1.Material: Fluorinated Ethylene Propylene
 - 2.2.Wall Thickness: 0.008"
 - 2.3.Color Code: Black, Black/White, Green/Yellow
- 3. Assembly**
 - 3.1.Cable Lay Length: 1.75" LHL (6.83 tw/ft)
- 4. Jacket**
 - 4.1.Material: Fluorinated Ethylene Propylene
 - 4.2.Wall Thickness: 0.013"
 - 4.3.Diameter: 0.143"
 - 4.4.Color: Black
 - 4.5.Ripcord: N/A
 - 4.6.Weight: 27 Lbs/Mft
- 5. Markings**
 - 5.1.Type: N/A
 - 5.2.Legend: N/A
 - 5.3.Footage Markers: N/A
- 6. Mechanical Characteristics**
 - 6.1.Operating Voltage: 600V RMS Maximum
 - 6.2.Operating Temperature: -75°C to 200°C
 - 6.3.Flexing Bend Radius: 15 x Cable Diameter
 - 6.4.Static Bend Radius: 4 x Cable Diameter
- 7. Standards**
 - 7.1.All materials used in the manufacture of this cable are RoHS II & REACH compliant
 - 7.2.Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION