

LARGE FLAT TINNED COPPER

* Denotes QQB575 construction

NOTE: When bare copper is required add (B) to our part #

EXAMPLE - 240B

CCC NO.	NOMINAL FLAT WIDTH	NOMINAL THICKNESS	AWG. OF INDIV ENDS	NO. OF STRANDS (CARRIER)	NO. OF WIRES PER STRAND	TOTAL NO. OF INDIV. WIRES	APPROX. AWG. EQUIV.	NOMINAL CIRCULAR MILLS	CURRENT CARRYING CAPACITY (AMPS)	APPROX. SHIPPING WEIGHT (LBS.)
240 *	1/2"	0.08	30	24	10	240	6	24000	93	83
242 *	5/8"	0.085	30	24	15	360	5	36000	120	121
244	3/4"	0.11	30	24	20	480	3	48000	145	170
246	7/8"	0.12	30	24	24	576	3	57600	165	193
248	15/16"	0.13	30	24	26	624	2	62400	170	210
250	15/16"	0.13	30	24	27	648	2	64800	175	225
252	1"	0.14	30	24	32	768	1	76800	195	270
260	3/4"	0.05	30	48	5	240	6	24000	93	88
262 *	1 3/8"	0.06	30	48	7	336	5	33600	100	129
264	1"	0.07	30	48	8	384	4	38400	120	137
266	1 1/4"	0.08	30	48	10	480	3	48000	145	168
268 *	1 1/2"	0.08	30	48	11	528	3	52800	145	192
270	7/8"	0.09	30	48	12	576	2	57600	150	200
272	1 3/8"	0.09	30	48	14	672	2	67200	165	230
274	1 1/2"	0.1	30	48	16	768	1	76800	180	265
276	1 5/8"	0.11	30	48	18	864	1	86400	200	283
278	1 3/8"	0.12	30	48	22	1056	1/0	105600	235	362
279	1 3/4"	0.13	30	48	26	1248	2/0	124800	250	430
280	2"	0.13	30	48	28	1344	2/0	134400	255	464
282	2"	0.14	30	48	32	1536	3/0	153600	290	530

284	2"	0.15	30	48	35	1680	3/0	168000	320	570
286	2 3/8"	0.175	30	48	44	2112	4/0	211200	370	730
287	3"	0.19	30	48	47	2256	4/0	225600	390	780
288	2 1/2"	0.19	30	48	52	2496	250 MCM	249600	410	900

Continental Cordage Corporation



INTERNATIONAL WIRE
Continental Cordage
 315-655-9800 phone
 315-655-9686 fax