



Hueson Wire  
 38 Sutton Street  
 Northbridge, MA 01534  
 508-234-6372  
 bhanlon@huesonwire.com

Issue Date: 1/27/2016

Issue: 1

**Construction**

**C5615**

Description: 9/C Composite 22 7/30 TC 4 pr + 1 Cond		Diam. (In)
Component:	9 Conds 22 7/30 Tinned Copper (4 Pairs + 1 Single)	
Conductor:	22 AWG 7/30 Tinned Copper to ASTM-B33	0.030"
Insulation:	0.009" General Purpose PVC	0.048"
Twist Pairs:	Twist Components into 4 Pairs	0.079"
Color Code:	Black + Red, Green + White, Blue + Yellow, Brown + Orange	0.079"
Cable Assembly:	Twist 4 Pairs per Color Code Above with Once Single Violet Conductor in Center	0.215"
Fillers	Fibrillated polypropylene fillers for roundness	0.215"
Tape:	Non-Woven Separator Tape for Strip-Ability	0.220"
Jacket:	0.032" Premium Grade UL PVC Jacket Pressure Extrude	0.285"
Jacket Color:	Black	0.285"
Print: White Ink	<b>TEEJET</b>	

Specifications:	Temp	Voltage	Flame	UL List
	80°C	300	VW-1	CM

**Environmental Compliance**

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65: