



Specification

Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
 www.huesonwire.com

Issue Date: 1/27/2016

Issue: 1

Construction

C5617

Description: 4/C Composite 2/C 16(26) + 2/C 20(19) PVC/PVC		Diam. (In)
Components:	4 Total conductors	
Conductor 1:	2 Conductors 16 26/30 TC to ASTM B 33-74	0.066 "
Insulation:	0.015" Premium Grade PVC	0.096 "
Color Code	Black, Red	0.096 "
Conductor 2:	2 Conductors 20 19/32 TC to ASTM B 33-74	0.035 "
Insulation:	0.015" Premium Grade PVC	0.07 "
Color Code	Yellow, Green	0.07 "
Cable Assembly:	Bunch Cable 2 Cond's 18(16) with 2 Conds 20(19)	0.201 "
Fillers	Fibrillated Polypropylene core for roundness (optional)	0.201 "
Tape:	Non-Woven Separator Tape for Strip-Ability (Optional)	0.204 "
Jacket:	0.0305" Premium Grade PVC Jacket Pressure Extrude	0.265 "
Jacket Color:	Black	0.265 "
Print: (White)	TEEJET	

Specifications:	Temperature	Voltage
	105°C	300V

Environmental Compliance

EU Directive 2002/95/EC(RoHS):
 All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

REACH Regulation (EC 1907/2006):
 This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

California Prop 65:
 The outer surface of materials used to manufacture this part meet requirements of California Prop. 65