



Issue Date: 1/13/2016

Construction

Issue: 2

Description:	5/C 12 (65) TC mPPE/PUR	Diam. (In)
Component:	5 Conductors	
Conductor:	12 AWG 65/30 Tinned Copper Smoothbunch	0.09"
Insulation:	0.012" Halogen Free mPPE (Modified Polyphenylene)	0.114"
Color Code:	Red, Black, Yellow, Black/White, Yellow/Black	0.114"
Cable Assembly:	5 Conductors Bunched Cabled	0.308"
Tape:	Non-Woven Separator Tape for Strip-Ability (optional)	0.311"
Jacket:	0.040" Halogen Free Polyurethane	0.391"
Jacket Color:	Gray	0.391"

Print: E174416 RU AWM-21755 90°C 600V - - - cRU AWM I/II A B 90°C 600V FT-2
Apollo Video Technology Zero Halogen Rail Cabling

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>
UL	AWM- 21755	90°C	600V	FT-2
Canadian cRU	AWM	90°C	600V	FT-2

Environmental Compliance

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65: