



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 10/11/2016
Issue: 1

Construction

Description: 4/C 22 7/30TC PVC/PVC		Diam. (In)
Component:	4 Conductors	
Conductor:	22 AWG 7/30 Tinned Copper to ASTM-B33	0.03"
Insulation:	0.01" Premium Grade PVC	0.05"
Color Code:	Black, Red, White, Green	0.05"
Cable Assembly:	4 Conductors Bunched Cabled	0.121"
Fillers:	Fibrillated polypropylene or solid fillers for roundness (optional)	0.121"
Tape:	Non-Woven Separator Tape for Strip-Ability (optional)	0.124"
Jacket:	0.04" PVC,Oil, Gas, Moisture and UV Resistant Pressure Extruded	0.204"
Jacket Color:	Black	0.204"

Print: Not Required

Specifications:
 Insulation: Transportation Automotive Grade PVC to SAE-J-1128 Type GPT
 Jacket: Transportation Grade PVC Resistant to Oil, Gas, Moisture, Flame and UV

Environmental Compliance

- EU Directive 2011/95/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65:

IQ160434