

# DATA CABLES



## LiYY Multiconductor signal and control cable DIN Color code

SAB BRÖCKSKES · D-VIERSEN · LiYY 36 x 0.14 mm<sup>2</sup> CE



Marking for LiYY 03053614:

SAB BRÖCKSKES · D-VIERSEN · LiYY 36 x 0.14 mm<sup>2</sup> CE

LiYY is an unshielded, multiconductor signal and control cable recommended for use in European designed computer, data transmission and office equipment, process control and instrumentation.

### Construction:

<b>Conductor:</b>	bare copper strands with reference to DIN VDE 0812
<b>Insulation:</b>	PVC, Y12 acc. to DIN VDE 0207 part 4
<b>Color code:</b>	with reference to DIN 47100
<b>Stranding:</b>	in layers
<b>Jacket material:</b>	PVC, YM1 acc. to DIN VDE 0207 part 5
<b>Jacket color:</b>	gray

### Outstanding features:

- flexible
- small outer diameter
- small bending radius

### Technical data:

<b>Peak operating voltage:</b>	< 24 AWG = max. 350 V ≥ 24 AWG = max. 500 V
<b>Testing voltage:</b>	< 24 AWG = 800 V ≥ 24 AWG = 1200 V
<b>Min. bending radius</b>	
<i>fixed installation:</i>	5 x O.D.
<i>free movement:</i>	10 x O.D.
<b>Capacitance:</b>	see page N/8
<b>Radiation resistance:</b>	8 x 10 <sup>7</sup> cJ/kg
<b>Temperature range</b>	
<i>static:</i>	-30/+70 °C
<i>flexing:</i>	-5/+70 °C
<b>Burning characteristics:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2
<b>Oil resistance:</b>	acc. to internal standard, see page N/27
<b>Chem. resistance:</b>	see page N/9
<b>Color code:</b>	see see page N/24
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/28

F  
10

item no.	no. of conductors	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mt	item no.	no. of conductors	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mt	item no.	no. of conductors	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mt
<b>▶ 26 AWG (≈18/38) • 0.14 mm<sup>2</sup></b>					<b>▶ 24 AWG (≈14/34) • 0.25 mm<sup>2</sup></b>					<b>▶ 22 AWG (≈7/30) • 0.34 mm<sup>2</sup></b>				
03050214	2	0.122	3.1	9	03050225	2	0.134	3.4	11	03050234	2	0.157	4.0	15
03050314	3	0.130	3.3	10	03050325	3	0.142	3.6	13	03050334	3	0.165	4.2	18
03050414	4	0.138	3.5	11	03050425	4	0.154	3.9	16	03050434	4	0.181	4.6	22
03050514	5	0.150	3.8	14	03050525	5	0.165	4.2	19	03050534	5	0.197	5.0	28
03050614	6	0.161	4.1	17	03050625	6	0.181	4.6	23	03050634	6	0.217	5.5	33
03050714	7	0.161	4.1	17	03050725	7	0.181	4.6	24	03050734	7	0.217	5.5	34
03050814	8	0.185	4.7	22	03050825	8	0.205	5.2	30	03050834	8	0.256	6.5	45
03051014	10	0.201	5.1	23	03050925	9	0.220	5.6	34	03051034	10	0.280	7.1	48
03051214	12	0.209	5.3	26	03051025	10	0.232	5.9	34	03051234	12	0.287	7.3	56
03051414	14	0.217	5.5	30	03051225	12	0.240	6.1	39	03051434	14	0.311	7.9	66
03051614	16	0.236	6.0	36	03051425	14	0.252	6.4	44	03051634	16	0.327	8.3	75
03051814	18	0.248	6.3	40	03051625	16	0.264	6.7	50	03051834	18	0.346	8.8	83
03052014	20	0.260	6.6	44	03051825	18	0.280	7.1	56	03052034	20	0.362	9.2	92
03052114	21	0.272	6.9	46	03052025	20	0.299	7.6	64	03052134	21	0.394	10.0	103
03052414	24	0.287	7.3	49	03052125	21	0.311	7.9	67	03052434	24	0.417	10.6	111
03052514	25	0.303	7.7	53	03052425	24	0.331	8.4	73	03052534	25	0.425	10.8	114
03052714	27	0.303	7.7	56	03052525	25	0.339	8.6	75	03052734	27	0.425	10.8	122
03053014	30	0.311	7.9	60	03052725	27	0.339	8.6	80	03053034	30	0.441	11.2	132
03053214	32	0.323	8.2	65	03053025	30	0.350	8.9	88	03053234	32	0.457	11.6	141
03053614	36	0.335	8.5	72	03053225	32	0.362	9.2	93	03053634	36	0.476	12.1	157
03054014	40	0.358	9.1	80	03053625	36	0.394	10.0	110	03054034	40	0.508	12.9	175
03054414	44	0.374	9.5	85	03054025	40	0.417	10.6	122	03054434	44	0.531	13.5	186
03054814	48	0.398	10.1	97	03054425	44	0.437	11.1	129	03054834	48	0.539	13.7	200
03055014	50	0.406	10.3	100	03054825	48	0.445	11.3	138	03055234	52	0.571	14.5	224
03055214	52	0.406	10.3	103	03055025	50	0.457	11.6	144	03055634	56	0.587	14.9	239
03055614	56	0.417	10.6	111	03055225	52	0.457	11.6	149	03056134	61	0.606	15.4	257
03056114	61	0.429	10.9	118	03055625	56	0.469	11.9	159					
					03056125	61	0.484	12.3	171					

Continued on next page

E-mail: [info@sabcable.com](mailto:info@sabcable.com)



Web site: [www.sabcable.com](http://www.sabcable.com)