REV.	DESCRIPTION				DATE
1			1, adjust electrical performance, add PN		6/9/2010
2 3	Added second jacket for roundness and connector fit Change Primary Colors				7/15/2010
4			CR requirements		9/14/2010
5			or change and view of cable		12/1/2010
	sina reauireme				12/13/2010
(Orange Orange Blue	6 5 Yellow 9	Jacket	Black
Description inches				Dimensi inches	ons (Nom.) mm
-	th member:	Multi-Strand 7X19 1/16" 302/304 300 pound minimum break stren		0.064	1.63
2. Crossv		HDPE			
3. Condu		18 AWG 19/.0092" Tinned Copp		0.045	1.14
4. Insulat	ion:		ts requirements of SAE J1128 GXL	0.105	2.67
Cable:		(4) primaries around crossweb		0.300	7.62
5. Shield:		2 mil Aluminum/polyester spirally	/ applied	0.305	7.75
6. Drain		Braided 3X40 AWG TC .053" X .			
7. Braid:		36 AWG Tinned copper 85% mir		0.325	8.26
	11-				
8. Inner J		Extruded EXRAD XLE, .040" nor		0.405	10.30
9. Outer J	Jacket:	Extruded EXRAD XLE, .040" nor	n wall	0.485	12.33
		Both jackets to be fused and not	readily seperable		
Flame Bend F * Impeda * ACR: Cable * Electric	e Rating: Rating: Radius: ance: Pull Strength: C cal performance		r /blue) and (orange/yellow) roduction lots. Parameters to be adjusted aft		
Cable			the end of the cable as it is payed off a spoo	l.	
	TITLE	±			
					-
CHAMPLAIN CA	BLE	Dataclear Eth	nernet 100-BaseT2 Cab	ie for OBI	
175 HERCULES DRIVE COLCHESTER, VT 05446		4 Cor	nductor 18 AWG Shield	ed	
802-654-4200 UNLESS OTHERWISE SPE	,	DRN. DATE 2/15/2010			
DIMENSIONS AND TOLER ARE IN INCHES	ANCES CKD.	5	DATE		
ARE IN INCHES		Bruce Sinnott	2/15/2	2010	
DO NOT SCALE THIS DRAV	WING SIZE	PART NUMBER	DOCUMENT NUMBER		
		45 07774			
	A	15-07774	13	3931	

ETF-011 Owner: RF Business Unit Manager - Approved By: VP of Operations / 27 February 2004