

# Product Specification

Part No.:B1571-780		Color																														
<p><b>Cross Section</b></p>		Insulation color: Black / Brown / Red / Orange / Yellow / Green / Blue / Violet Gray / White / Light Blue / Pink / Light Green / Light Gray																														
<p><b>Marking</b></p> Nil		<p><b>Performance</b></p> <p><b>Electrical Characteristics:</b></p> <table border="0"> <tr> <td>Max DC Conductor Resistance at 20°C (Ω/km)</td> <td>239.0</td> </tr> </table>		Max DC Conductor Resistance at 20°C (Ω/km)	239.0																											
Max DC Conductor Resistance at 20°C (Ω/km)	239.0																															
<p><b>Description</b></p> <table border="0"> <tr> <td>Rated Voltage (V)</td> <td>30</td> </tr> <tr> <td>Rated Temperature (°C)</td> <td>80</td> </tr> <tr> <td>Product Standard Certification</td> <td>UL</td> </tr> <tr> <td>Flammability Test</td> <td>UL VW-1 &amp; CSA FT1</td> </tr> </table> <p><b>Application</b> For general purpose internal wiring of electronic equipment</p> <p><b>Reference Standard</b> UL758, UL1581 &amp; CSA C22.2 No.210.2</p>		Rated Voltage (V)	30	Rated Temperature (°C)	80	Product Standard Certification	UL	Flammability Test	UL VW-1 & CSA FT1	<p><b>Mechanical Characteristics:</b></p> <table border="0"> <tr> <td><b>Test Object</b></td> <td></td> <td><b>Insulation</b></td> </tr> <tr> <td>Test Material</td> <td></td> <td>SR-PVC</td> </tr> <tr> <td>Before</td> <td>Tensile Strength (Mpa)</td> <td>≥ 20.7</td> </tr> <tr> <td>Aging</td> <td>Elongation (%)</td> <td>≥ 100</td> </tr> <tr> <td>Aging Condition</td> <td></td> <td>113±2°C x 168 hrs</td> </tr> <tr> <td>After</td> <td>Tensile Strength (Mpa)</td> <td>≥ 70% of original</td> </tr> <tr> <td>Aging</td> <td>Elongation (%)</td> <td>≥ 70% of original</td> </tr> </table>		<b>Test Object</b>		<b>Insulation</b>	Test Material		SR-PVC	Before	Tensile Strength (Mpa)	≥ 20.7	Aging	Elongation (%)	≥ 100	Aging Condition		113±2°C x 168 hrs	After	Tensile Strength (Mpa)	≥ 70% of original	Aging	Elongation (%)	≥ 70% of original
Rated Voltage (V)	30																															
Rated Temperature (°C)	80																															
Product Standard Certification	UL																															
Flammability Test	UL VW-1 & CSA FT1																															
<b>Test Object</b>		<b>Insulation</b>																														
Test Material		SR-PVC																														
Before	Tensile Strength (Mpa)	≥ 20.7																														
Aging	Elongation (%)	≥ 100																														
Aging Condition		113±2°C x 168 hrs																														
After	Tensile Strength (Mpa)	≥ 70% of original																														
Aging	Elongation (%)	≥ 70% of original																														
<p><b>Construction</b></p> <table border="0"> <tr> <td>1 Core</td> <td></td> </tr> <tr> <td><b>Conductor</b></td> <td>Stranded Tinned Copper</td> </tr> <tr> <td>AWG</td> <td>28</td> </tr> <tr> <td>Construction (mm)</td> <td>7/0.127</td> </tr> <tr> <td>Stranded Dia. (mm)</td> <td>0.38</td> </tr> <tr> <td><b>Insulation</b></td> <td>SR-PVC</td> </tr> <tr> <td>Min. Thickness (mm)</td> <td>0.08</td> </tr> <tr> <td>Nom. Thickness (mm)</td> <td>0.10</td> </tr> <tr> <td>Insulation Dia. (±0.04mm)</td> <td>0.56</td> </tr> </table>		1 Core		<b>Conductor</b>	Stranded Tinned Copper	AWG	28	Construction (mm)	7/0.127	Stranded Dia. (mm)	0.38	<b>Insulation</b>	SR-PVC	Min. Thickness (mm)	0.08	Nom. Thickness (mm)	0.10	Insulation Dia. (±0.04mm)	0.56													
1 Core																																
<b>Conductor</b>	Stranded Tinned Copper																															
AWG	28																															
Construction (mm)	7/0.127																															
Stranded Dia. (mm)	0.38																															
<b>Insulation</b>	SR-PVC																															
Min. Thickness (mm)	0.08																															
Nom. Thickness (mm)	0.10																															
Insulation Dia. (±0.04mm)	0.56																															
<p><b>Engineer Review</b> P/N:RNSK-1571-483BLU Rev.:0</p>		<p><b>Sample Record</b></p> <table border="0"> <tr> <td>Sample No. :</td> <td></td> </tr> <tr> <td>Original spec no.:</td> <td>Rev.:</td> </tr> <tr> <td>Ref. spec No. : SK-B1571-780</td> <td>Rev.: 0</td> </tr> </table>		Sample No. :		Original spec no.:	Rev.:	Ref. spec No. : SK-B1571-780	Rev.: 0																							
Sample No. :																																
Original spec no.:	Rev.:																															
Ref. spec No. : SK-B1571-780	Rev.: 0																															
		<p><b>Revision History</b></p>																														
		Prepared by:   Yaqin Mo   2012/11/13   Table No.:T100   Rev.: 0 Approved by:   CICICHENG   2012/11/13   Page 1 of 1																														