

**1. CONDUCTOR:**

- 1.1 Size and Material: 22 7/30 AWG tin-plated copper wire.
- 1.2 O.D.: .030" nom.

**2. INSULATION:**

- 2.1 Extruded silicone rubber.
- 2.2 Marking on the insulation: As per NEMA Standard.
- 2.3 O.D.: .061" nom.
- 2.4 Color: As per order (replace X in the part number and at the end of the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 150°C


**4. REFERENCES:**

- 4.1 NEMA Standards Publication No. HP 6.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.	This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done:	<i>Daniel Curson</i>						
		Date:	March 11, 2016						
		Verified:	<i>David Holt</i>						
		Date:	March 11, 2016						
		Size:	A	Scale:	---	Page:	1 of 1		
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com			Description:		<b>HP 6-S-HFBX</b>		
		Code Ident. No:	<b>57104</b>		Specification No.:	<b>F01034-X</b>		Rev.	---