



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 3/16/2016
Issue: 1

Construction

Description: 3/C 12 (65/30) TC mPPE/TPV		Diam. (In)
Component:	3 Conductors	
Conductor:	12 AWG 65/30 Tinned Copper to ASTM B-8	0.09"
Insulation:	0.012" mPPE UL Approved	0.114"
Color Code:	Black, White, Green/Yellow	0.114"
Cable Assembly:	3 Conductors Bunched Cabled	0.245"
Fillers:	Fibrillated polypropylene or solid fillers for roundness (optional)	0.245"
Tape:	Non-Woven Separator Tape for Strip-Ability (optional)	0.248"
Jacket:	0.04" Santoprene TPV	0.328"
Jacket Color:	Black	0.328"

Print: E174416 RU AWM STYLE 20328 105C 600V FT-2 - - - c(RU) AWM I/II A/B 90C 600V FT-2

Specifications:	AWM Style	Temp	Voltage	Flame	UL List
UL	20328		600V	105°C	FT-2
Canadian cRU	AWM		600V	90°C	FT-2

Environmental Compliance

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65:

IQ160119 -C



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
bhanlon@huesonwire.com

Issue Date: 3/16/2016
Issue: 1

Drawing/Rotation:

