



Hueson Wire  
38 Sutton Street  
Northbridge, MA 01534  
508-234-6372  
[bhanlon@huesonwire.com](mailto:bhanlon@huesonwire.com)

Issue Date: 5/5/2016  
Issue: 1

## Construction

Description:	2/C 22 7/30 TC SR-PVC/PVC OAS + Dr	Diam. (In)
Component:	2 Conductors	
Conductor:	22 AWG 7/30 Tinned Copper to ASTM-B33	0.03"
Insulation:	0.009" SR-PVC	0.048"
Color Code:	Black, White	0.048"
Cable Assembly:	2 Conductors Bunched Cabled	0.096"
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	0.096"
Drain Wire:	22 7/30 TC	0.096"
Shield:	Aluminum Mylar Foil Shield - 100% Coverage - 25% min Overlap	0.099"
Jacket:	0.024" PVC CMG FT-4	0.147"
Jacket Color:	Gray	0.147"

Print: E194074 2/C 22 AWG SHIELDED 75C (UL) TYPE CM - - - LL109360 CSA TYPE CMG 60C FT4

### Specifications:

UL Type CM                      Temperature: 75°C (UL)                      (Non UL) Voltage 600V  
CSA Type CMG, FT4                      60°C (CSA)                      PVC Temp -20°C to +105°C

### Environmental Compliance

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65:

IQ160140



Hueson Wire  
38 Sutton Street  
Northbridge, MA 01534  
508-234-6372  
[bhanlon@huesonwire.com](mailto:bhanlon@huesonwire.com)

**Issue Date:** 5/5/2016

**Issue:** 1

**Drawing/Rotation:**

IQ160140