



Features

- Low Smoke Zero Halogen Design
- RoHS compliant insulation
- Thermoset insulation for enhanced thermal stability
- Specially formulated insulation for exceptional long term water resistance
- Superior flame retardance
- Excellent mechanical properties
- Tin-coated copper conductors for improved terminations and corrosion resistance
- Reduced size and weight for increased raceway capacity
- Easy strippability
- Low friction surface for reduced pulling tension
- Rated for CT use 1/0 and larger

Performance Standards

- Insulation in accordance with ICEA and UL standards
- Passes IEEE 1202/FT4 vertical tray flame test and ICEA 70,000 BTU/hr vertical flame test
- Passes UL VW-1**
- Passes vertical flame test Type A as defined in ICEA S-95-658 (6.8.2)
- UL listed as Type ST1 (Limited Smoke)
- UL approved 90° for both wet and dry locations
- UL listed for sunlight resistance (Black)
- UL Listed as gasoline and oil resistant
- Meets the requirements of NFPA 130 & 502 as applicable

Construction

Conductor: Annealed, tin-coated copper, Class "B" strand per ASTM B-8 & B-33 (Available as solid conductors when required)

Insulation: Flame retardant low Smoke Zero Halogen crosslinked polyolefin

Separator Tape: Helically applied polyester (where required)

Color: Black (Available in pigmented colors or colored stripes)

* Rated 90°C for normal operation in wet and dry locations, 130°C for emergency overload conditions, and 250°C for short circuit conditions.

** #10 AWG and larger.

Scope

Firewall® LSZH XHHW-2 is a one conductor, unjacketed, power cable. Its tough thermoset construction allows for its use in demanding applications without additional jacketing protection. It is intended for low voltage power and lighting functions and may be installed in trays, ducts and conduits.

Firewall® LSZH XHHW-2 Power & Lighting Cable



Low Smoke Zero Halogen
90°C*, 600 Volt
NEC Type XHHW-2, UL Listed
NFPA 130 & 502

Product Code	Conductor Size	Number of Strands	Insulation Thickness		Nominal Overall Diameter		Approximate Net Weight (Lbs/M)
			(Inch)	(mm)	(Inch)	(mm)	
P46-2140	14 AWG	Solid	.030	.76	.13	3.2	18
P46-2120	12 AWG	Solid	.030	.76	.14	3.6	27
P46-2110	10 AWG	Solid	.030	.76	.16	4.2	39
P46-0140	14 AWG	7	.030	.76	.13	3.3	19
P46-0120	12 AWG	7	.030	.76	.15	3.8	28
P46-0110	10 AWG	7	.030	.76	.18	4.6	40
P46-0080	8 AWG	7	.045	1.14	.24	6.1	70
P46-0060	6 AWG	7	.045	1.14	.27	6.9	105
P46-0040	4 AWG	7	.045	1.14	.32	8.1	160
P46-0020	2 AWG	7	.045	1.14	.38	9.7	240
P46-0010	1 AWG	19	.055	1.40	.44	11.2	305
P46-0100	1/0 AWG	19	.055	1.40	.48	12.2	375
P46-0200	2/0 AWG	19	.055	1.40	.52	13.2	470
P46-0300	3/0 AWG	19	.055	1.40	.57	14.5	590
P46-0400	4/0 AWG	19	.055	1.40	.63	16.0	730
P46-0250	250 kcmil	37	.065	1.65	.70	17.8	870
P46-0350	350 kcmil	37	.065	1.65	.80	20.3	1200
P46-0500	500 kcmil	37	.065	1.65	.93	23.6	1680
P46-0600	600 kcmil	61	.080	2.03	1.05	26.7	2031
P46-0750	750 kcmil	61	.080	2.03	1.14	28.9	2499



Marmon Engineered Wire & Cable LLC
A Berkshire Hathaway Company