


LUTZE TOP-T Fittings PG

Plastic PG



Characteristics

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- Temperature range -20°C - +100°C/
-4°F - +212°F
- Max temporary temperature up to +150°C/+300°F
- Protection class IP68

Specifications

Connecting thread PG as per DIN 40430

Material Polyamide 6

Seal CR Chloroprene Rubber

Color Black RAL 9005
Gray RAL 7001

Item Specific Approvals

- UL Recognized (R) or UL Listed (L), as per table

Part No.	Thread	Clamping Range Ø inches	Clamping Range Ø mm	TL mm	D/SW mm	TD mm	H mm	UL R / L
BLACK								
FPPG7B	PG 7	0.118-0.256	3-6.5	8	15	12.4	23	R
FPPG9B	PG 9	0.157-0.315	4-8	8	19	15.1	26.5	R
FPPG11B	PG 11	0.197-0.394	5-10	8	22	18.5	22	R
FPPG13B	PG 13.5	0.236-0.472	6-12	10	24	20.3	29.5	L
FPPG16B	PG 16	0.394-0.551	10-14	10	27	22.5	32.5	L
FPPG21B	PG 21	0.512-0.709	13-18	11	33	28.1	35	L
FPPG29B	PG 29	0.709-0.984	18-25	11	42	37	42	L
FPPG36B	PG 36	0.866-1.260	22-32	13	53	46.8	52	L
FPPG42B	PG 42	1.181-1.496	30-38	13	60	54	54.5	L
FPPG48B	PG 48	1.339-1.732	34-44	14	65	59	54.5	L

GRAY								
Part No.	Thread	Clamping Range Ø inches	Clamping Range Ø mm	TL mm	D/SW mm	TD mm	H mm	UL R / L
FPPG7G	PG 7	0.118-0.256	3-6.5	8	15	12.4	23	R
FPPG9G	PG 9	0.157-0.315	4-8	8	19	15.1	26.5	R
FPPG11G	PG 11	0.197-0.394	5-10	8	22	18.5	22	R
FPPG13G	PG 13.5	0.236-0.472	6-12	10	24	20.3	29.5	L
FPPG16G	PG 16	0.394-0.551	10-14	10	27	22.5	32.5	L
FPPG21G	PG 21	0.512-0.709	13-18	11	33	28.1	35	L
FPPG29G	PG 29	0.709-0.984	18-25	11	42	37	42	L
FPPG36G	PG 36	0.866-1.260	22-32	13	53	46.8	52	L
FPPG42G	PG 42	1.181-1.496	30-38	13	60	54	54.5	L
FPPG48G	PG 48	1.339-1.732	34-44	14	65	59	54.5	L

REDUCED CLAMPING RANGE

FPPG7G-R	PG 7	0.079-0.197	2-5	8	15	12.4	22	
FPPG9G-R	PG 9	0.079-0.236	2-6	8	19	15.1	25	
FPPG11G-R	PG 11	0.118-0.276	3-7	8	22	18.5	28	
FPPG13G-R	PG 13.5	0.197-0.354	5-9	10	24	20.3	29	
FPPG16G-R	PG 16	0.276-0.472	7-12	10	27	22.5	31	
FPPG21G-R	PG 21	0.354-0.630	9-16	11	33	28.1	35	
FPPG29G-R	PG 29	0.472-0.787	12-20	11	42	37	40	
FPPG36G-R	PG 36	0.787-1.024	20-26	13	53	46.8	49	