

Technical
Data Sheet
10/01/1999
RR44476
Rev. 0

I. DESCRIPTION:

-----

3/0 AWG STRANDED TINNED COPPER - EPDM INSULATED

II. ELECTRICAL CHARACTERISTICS:

-----

UL STYLE: 3340 AND 3374

UL RATING: 600 VOLTS, 125 DEG C FLEX/

150 DEG C NO FLEX

CSA TYPE: CL 1254

CSA RATING: 600 VOLTS, 125 DEG. C

MIL STANDARD:
MIL SPEC RATING:
NONE

III. PHYSICAL CHARACTERISTICS:

-----

AWG SIZE: 3/0 AWG

STRANDING: 630X#26 AWG TINNED COPPER

INSULATION MATERIAL: EPDM

INSULATION THICKNESS: .095" MIN. AVG. DIAMETER: .758" +/- .009"

TEMPERATURE RATING: 150 DEG. C

IV. OTHER:

----

SEPARATOR BETWEEN STRANDING AND INSULATION (INSULATION BONDING)

© 2017 Belden, Inc. All rights reserved. All information contained herein is confidential. Its use is restricted to authorized Belden personnel or authorized vendors or customers of Belden. Under no circumstances shall this document be duplicated in any form or shown to/discussed with unauthorized personnel without the expressed written consent of Belden. Although Belden makes every reasonable effort to ensure accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability our suitability for a given purpose. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory, or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence, or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden reserves the right to change any specification in the interest of product enhancement. This cable complies with the EU-RoHS directive 2002/95/EC (restrictions on hazardous substances).