

## GENERAL PRODUCT SPECIFICATION Phone 800-316-8877 Fax 978-368-1275 www.jamesmonroewire.com

**Description:** Two 18 AWG Insulated Conductors

Overall PVC Jacket

**Date:** 5/13/16

JM Part Number: TBD

Reference: TBD

Components Two 18 AWG Insulated Conductors

Conductor: 18 AWG, 41/34 bare copper

Insulation: .010" nominal wall of PVC (see color code) .065"

**Overall Cable Construction** 

Cabling: Two 18 AWG conductors twisted together

Separator: Tissue tape

Jacket: .040" nominal wall of pressured extruded Black PVC .215" ± .010"

Print (White Inkjet, 12 Inch Intervals Maximum)

E66440 2/C 18 AWG 5\\ AWM STYLE 2517 105C 300V VW-1 --- LL41103 CSA AWM I/II A/B 105C 300V FT1 --- ROHS

**Color Code** 

1. Red 2. Black

Requirements

Temperature: -40C° to 105C (Static) Approvals: AWM Style 2517

Voltage: 300V CSA AWM, FT1

Material are RoHS Compliant

(2011/65/EU)

Written By:	rac/scs	5/13/2016	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				