



PRODUCT DATA SHEET

Controlled Document – Engineering Drive

1530 Shields Drive
 Waukegan, IL 60085
 Toll-Free: (800) 323-9355
 Fax: (847) 689-1192

PART NUMBER: L40008-1

DESCRIPTION: 2/C 18 AWG SHIELDED COMMERCIAL AUDIO, CONTROL AND INSTRUMENTATION CABLE 80C 300V OR 60C 300V AWM STYLE 2092 NON-PLENUM RATED

CUSTOMER:

CONSTRUCTION: 18 AWG 19 STRAND TC 2 CONDUCTORS TWISTED

INSULATION: POLYETHYLENE (Heavy Wall)

COLOR CODE: BLACK, CLEAR

SHIELD/DRAIN: ALUMINUM/POLYESTER FOIL (OUT); 20AWG 7 STRAND TC DRAIN

ASSEMBLY: 2 CONDUCTORS TWISTED, SHIELDED AND JACKETED

JACKET: PVC GRAY (.028 Nom Wall)

DIAMETER: 0.222" Nominal

CABLE WT: 31 Lbs/1000 Ft Approx (Net Weight)

PRINT LEGEND: 18AWG E57497 C(UL)US CM/CL3/FPL OR AWM 2092 300V -- CMH FT1 MADE IN USA
 ROHS-2 COMPLIANT

FOOTAGE MARKS: SEQUENTIALLY FOOT-PRINT TO WHATEVER THE PUT-UP IS IN
 ASCENDING/DESCENDING ORDER.

MARKER TAPE: NO

NEC: CM/CL3/FPL / FOR PLENUM RATED VERSION GO TO SPEC. NO. T40030 / P41111 /
 K40010 / T40064

COMPLIANCE: UL 444 CM by (UL) / NEC ARTICLE 800 / CSA C22.2 CMH by C(UL) / AWM 2092 / RoHS

FLAME TEST: UL 1685 Vertical Tray / CSA FT1

CAPACITANCE: 23.5 pF/Ft Nominal

VEL OF PROP: 66%

IMPEDANCE: 65 OHMS

RESISTANCE: 6.92 OHMS D.C. PER 1000 Ft @ 68 DEG. F Maximum

TEMP/VOLTAGE: 80C / 300V [60C 300V PER AWM STYLE 2902]

MISC: MADE IN USA

Specification Issue Date: 1/14/16	Rev Level:	ERF:	ECN:	Designed by:
-----------------------------------	------------	------	------	--------------

Complies with EU Dir. 2011/65/EU (RoHS-2).
 The customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditional upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire.
 Any information contained herein shall not be disclosed to any party without the written consent of Southwire.