

1. CONDUCTOR (2):

- 1.1 Size and Material: 18 AWG, 19 strands, tin-plated copper wire.
- 1.2 O.D.: .044" nom.

2. INSULATION:

- 2.1 Extruded special ETFE (Tefzel® 750).
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .064" nom.
- 2.4 Color code: black, white.

3. CABLING:

- 3.1 The two wires are twisted together (11 twists per foot).
- 3.2 O.D.: .128" nom.

4. REFERENCES:


- 4.1 UL Subject 758 (AWM), Style 10086 (inner wires only).
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B (inner wires only).

5. PERFORMANCE:

- 5.1 Voltage rating: 600 VAC R.M.S.
- 5.2 Temperature rating: 150°C

CUSTOMER APPROVAL

Sign: _____
 Date: _____

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>Daniel Curson</i>		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com		
								Date: May 17, 2016				
								Verified: <i>David Lott</i>		Description: 2(XTL10Z1819/0092) 0-9 (11 TPF)		
								Date: May 18, 2016				
UNCONTROLLED DOCUMENT A later revision of this specification may exist.								Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F04961-S