



Hueson Wire  
 38 Sutton Street  
 Northbridge, MA 01534  
 508-234-6372  
[bhanlon@huesonwire.com](mailto:bhanlon@huesonwire.com)

**Issue Date:** 5/24/2016  
**Issue:** 1

**Construction**

<b>Description:</b> 2/C 14 41/30 PVC/PVC SJTOW Gray		<b>Diam. (In)</b>
<b>Component:</b>	2 Conductors	
<b>Conductor:</b>	14 AWG 41/30 Bare Copper to ASTM B-174	0.075"
<b>Insulation:</b>	0.03" Premium Grade PVC	0.135"
<b>Color Code:</b>	Black, Red	0.135"
<b>Cable Assembly:</b>	2 Conductors Bunched Cabled	0.27"
<b>Fillers</b>	Fibrillated polypropylene or solid fillers for roundness (optional)	0.27"
<b>Drain Wire:</b>	No Drain	0.27"
<b>Shield:</b>	Aluminum Mylar Foil Shield	0.273"
<b>Tape:</b>	Non-Woven Separator Tape for Strip-Ability (optional)	0.273"
<b>Braid:</b>	Tinned Copper Braid Shield	0.273"
<b>Jacket:</b>	0.03" Premium Grade UL PVC	0.333"
<b>Jacket Color:</b>	Gray	0.333"

Print:

<b>Specifications:</b>	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>	<u>UL List</u>	
<b>UL</b>	AWM-2464	80°C	300	VW-1	CM	
Canadian cRU	AWM	80°C	300	FT-1	CMG	I/II A/B

**Environmental Compliance**

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65:

IQ160182



Hueson Wire  
38 Sutton Street  
Northbridge, MA 01534  
508-234-6372  
[bhanlon@huesonwire.com](mailto:bhanlon@huesonwire.com)

**Issue Date:** 5/24/2016  
**Issue:** 1

**Drawing/Rotation:**

IQ160182