



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2008

PRODUCT DATA SHEET

Part No: 74-389

CONSTRUCTION SPECIFICATIONS

Description AWM 3 Pair 22 AWG Unshielded
Conductor 22 AWG 7 Strand Tinned Copper - Concentric
Conductor Diameter 0.030"
Insulation Type Semi Rigid PVC
Insulation Thickness 0.008"
Conductor Identification Black/Red & Red, Black/White & White, Black/Green & Green
Ripcord Polyester Ripcord included under the cable jacket
Jacket Flame Retardant PVC
Jacket Thickness 0.040" (minimum average)
Overall Cable Diameter 0.249"
Jacket Print CSA AWM II A/B105C 600V FT4 LL67097 CMG 22 AWG 60C
 LL83251 RU AWM STYLE 2464 80C 300V E111002 ROHS
 (work order)

ELECTRICALS

Voltage 300V; CMG, AWM STYLE 2464 / 600V; AWM II
Conductor Resistance 16.6 Ohms/Mft @20C

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified *CSA C22.2 No. 214, Communications Cables
 *CSA C22.2 No. 210.2, Appliance Wiring Material Products
UL RECOGNIZED *UL 758, Appliance Wiring Material
Flame Test Rating CSA FT4
Temperature Rating 60C; CMG / 105C; AWM II / 80C; AWM STYLE 2464
ROHS Compliant
Cable Weight 48.69 kg/km
Copper Content 17.37 kg/km
Max Pull Tension 21 kgs
Min Bending Radius 3.00 inches (installed)
Min Installation Temp -20C

Rev. 000

14-Aug-13