

SJTOW

105°C PVC Cord. 300 Volts. Flexible Copper Conductors. PVC Insulation and Jacket. Rated for Hard-Usage Service Cords. Rated UL VW-1 and CSA FT1, FT2 Flame Resistant.



Image not to scale & for reference only. See Table 1 for Dimensions

CONSTRUCTION:

Conductors: Class K, Flexible bunch stranded bare copper per ASTM B3 and B174

Insulation: Polyvinyl Chloride (PVC)

Assembly: The insulated conductors are cabled together with paper fillers. A tissue paper is helically applied over the assembly to facilitate overall jacket removal. Note five conductor has center filler only.

Jacket: Black, PVC

APPLICATIONS AND FEATURES:

Southwire Type SJTOW Flexible Cords are permitted for use as specified by Article 400 and related articles of the 2011 National Electric Code. Some typical applications for Type SJTOW Cord include, but are not limited to: Wiring for industrial machinery such as washing machines and other large appliances, heavy-duty portable tools, motors and temporary electrical

SPECIFICATIONS:

- ASTM B3, B174
- UL 62 - Type SJTOW
- CSA C22.2 No. 49 - Type SJTOW

SAMPLE PRINT LEGEND: (Indent)

P/N 3011403 {UL} VW-1 E46194 MASTER-DESIGN SJTOOW 3/C 14 AWG (2.08mm²) 105°C DRY 60°C WATER RESISTANT 300V {CSA} FT1 FT2 LL90458 MASTER-DESIGN {SEQUENTIAL FOOTAGE MARKS} SEQ FEET

TABLE 1 - WEIGHTS & MEASUREMENTS

Stock Code	Cond. Size (AWG)	No. of Cond.	No. of Strands	Insulation Thickness (mils)	Jacket Thickness (mils)	Nominal OD (mils)	Nominal Weight (Lbs/Mft)	Color Code
599426xx	14	3	41	30	30	353	78	Brown, Light Blue, Green-Yellow

All dimensions are nominal and subject to normal manufacturing tolerances



Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | www.southwire.com

Copyright © 2016 Southwire Company, LLC. All Rights Reserved



Southwire[®]

OEMCS2019003 DATE: 1/9/2019 Rev: 0