



Specification Sheet

Lake Cable Part #: P228C

Description: 22 AWG 8 conductor 7 strand bare copper wire, plenum rated PVC insulation, unshielded, with an overall plenum rated PVC jacket

1. Conductor

- 1.1. AWG Size & Stranding: 22 AWG 7 Strands Class B
- 1.2. Material: Annealed Bare Copper
- 1.3. Conductor Count: 8 Conductors

2. Insulation

- 2.1. Material: Plenum Rated Polyvinylchloride
- 2.2. Wall Thickness: 0.007"
- 2.3. Color Code: Black, Red, White, Green, Brown, Blue, Orange, Yellow

3. Assembly

- 3.1. Nominal Lay Length: 2.25" LHL (5.33 Tw/Ft)
- 3.2. Shield: N/A
- 3.3. Drain Wire: N/A

4. Jacket

- 4.1. Material: Plenum Rated Polyvinylchloride
- 4.2. Wall Thickness: 0.014"
- 4.3. Diameter: 0.169"
- 4.4. Color: Natural
- 4.5. Ripcord: Yes
- 4.6. Weight: 33 Lbs/Mft

5. Markings

- 5.1. Type: Cable shall be permanently identified via surface inkjet print
- 5.2. Legend: LAKE CABLE E171197 22AWG 8C (UL) CMP C(UL)US or (UL) CL3P OR (UL) FPLP 75°C FT-6 "ROHS II" REACH MADE IN USA
- 5.3. Footage Markers: Yes

6. Standards

- 6.1. Refer to NEC (NFPA 70) article 725 and article 800 for installation guidelines
- 6.2. UL listed as type CL3P per UL standard 13, type CMP c(UL)us 75°C FT-6 per UL standard 444, and as type FPLP per UL standard 1424
- 6.3. All materials used in the manufacture of this cable are RoHS II & REACH compliant
- 6.4. Maximum Operating Voltage: 300V RMS
- 6.5. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION