

126-00065

Article Number: 126-00065

Arrowhead Mount Ties with Seal, 6.5" Long, 50lb Tensile, PA66HS, Natural, 500/bag



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 126-00065

**Type** T50SOSSFT6.5E-MS-MD

**Color** Natural (NA)

**Features and Benefits** One piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution. HellermannTyton's one piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

**Short Description** Arrowhead Mount Ties with Seal, 6.5" Long, 50lb Tensile, PA66HS, Natural, 500/bag

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 180 N

**Length L (Imperial)** 6.5 "

**Length L (Metric)** 163.0 mm

**Fixation Method** Arrowhead

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Width W (Imperial)** 0.18 "

**Width W (Metric)** 4.6 mm

**Height H (Imperial)** 0.63 "

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.5 mm

**Bundle Diameter Max. (Imperial)** 1.4 "

**Bundle Diameter Max. (Metric)** 35.0 mm

**Disc Diameter (Imperial)** 0.63 "

**Disc Diameter (Metric)** 16.0 mm

**Panel Thickness Max. (Imperial)** 0.06 "

**Panel Thickness Max. (Metric)** 1.6 mm

**Panel Thickness Min. (Imperial)** 0.03 "

**Panel Thickness Min. (Metric)** 0.7 mm

**Mounting Hole Diameter D (Imperial)** 0.25 - 0.27 "

**Mounting Hole Diameter D (Metric)** 6.25 - 6.75 mm

**Mounting Hole Diameter D Min.** 0.244 "

(Imperial) Mounting Hole Diameter D Max. 0.26 "  
(Imperial)

Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. (Metric) 6.75 mm

Mounting Hole Diameter D Min. (Metric) 6.25 mm

Thickness T (Metric) 1.3 mm

## Logistics and Packaging

---

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Carton Quantity 3000 Pieces

Weight (Metric) 1.51 kg

## Material and Specifications

---

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes