



Description: Four Conductor, 22 AWG
 Overall Foil Shield, Braid Shield
 and PU Jacket

Date: 6/15/2016

JM Part Number: JM57702
 Reference: 32019537

Components Four 22 AWG Insulated Conductors

Conductor: 22 AWG, 7/30 tinned copper
 Insulation: .009" nominal wall of Semi-Rigid PVC (see color code) .048"

Cable Construction

Cabling: Four Conductors cabled together, No Fillers
 Foil Shield: Aluminum-Mylar, Aluminum side OUT, 100% coverage
 Braid Shield: 36 AWG tinned copper braid, 60% coverage
 Separator: Tissue tape
 Jacket: .040" nominal wall of Matte Gray Pressured Polyurethane Jacket .215" ± .010"

Print

NONE

Color Code

1. Brown 2. White 3. Blue 4. Black

Requirements

Temperature: 80C Attributes: Sunlight Resistant
 Voltage: 300V Oil Resistant

Handwritten signature

6-21-16

Written By:	rac/ad	6/15/2016	Rev. 0	Initial Issue
Revised By:	scs	6/16/2016	Rev. 1	Added JM and Reference Numbers
Revised By:	ajd	6/20/2016	Rev. 2	Revised CC, braid coverage and added oil res per customer request
Revised By:				