

1. CONDUCTOR:

- 1.1 Size and Material: 20 10/30 AWG nickel-plated copper wire.
- 1.2 O.D.: .0355" nom.

2. INSULATION:

- 2.1 Extruded PFA.
- 2.2 Wall thickness: .010" nom.
- 2.3 Marking on the insulation: As per UL and CSA Standards.
- 2.4 O.D.: .0555" nom.
- 2.5 Color: As per order (replace X in the part number and at the end of the description by 0-9 color code).

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 250°C


4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 10362.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>David Lott</i>	 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com			
						Date: May 25, 2016						
						Verified: <i>Daniel Curson</i>		Description: XPA10N2010/30-X				
						Date: May 25, 2016						
UNCONTROLLED DOCUMENT A later revision of this specification may exist.								Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F01368-X