

ALPHA WIRE

Part Number: 16-2100

Issue:

Page 1 of 1 Pages

Issue Date:

6/24/2016

Cable Specification

<u>Component 1</u>	14 COND
<u>Conductor:</u>	20 (26/34) AWG TC
<u>Insulation:</u>	0.010" Wall, Nom. MPPE1
Color Code:	ALPHA WIRE COLOR CODE D
<u>Component 2</u>	4 COND
<u>Conductor:</u>	18 (16/30) AWG TC
<u>Insulation:</u>	0.018" Wall, Nom. MPPE1
Color Code:	ALPHA WIRE COLOR CODE D
<u>Final Assembly</u>	2 Components
Core Wrap:	NWP Tape, 25% Overlap, Min.
<u>Shield:</u>	TC BRAID Shield, 85% Coverage, Min.
<u>Jacket:</u>	0.032" Wall, Nom., PUZH
Jacket OD:	0.400"
Jacket Color:	BLACK
Jacket Separator:	TP Tape, 25% Overlap, Min.

Approvals

UL:	AWM/STYLE 21959
	60C OIL
	SUNRES
CSA:	c(RU) AWM I/II A/B
	FT2
MIL:	NONE
CE Compliant:	YES
ROHS Compliant:	YES
REACH Compliant:	YES

Miscellaneous

Temperature:	90 C
Voltage:	600 V _{RMS}
Put Ups:	1000 FT PUTUP
Requested Quantity:	1000Ft., 5000Ft.

Application Notes

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.