


TECHNICAL DATA SHEET

Description

Cable Part Code*	YJ70435
Cable Type	12x1.5 mm ² / 16 AWG PVC/PVC MULTI CORE CONTROL CABLE
Reference Standard	VDE 0285-525-2-51, DIN EN 50525-2-51, UL AWM 2464



Conductor

Conductor Material	Stranded Bare Copper
Conductor Size	1.5 mm ² / 16 AWG
Conductor Stranding Standard	IEC 60228 Class 5, DIN VDE 0295 Class 5

Insulation

No. of Cores	12
Insulation Material	PVC
Nom. Insulation Diameter(mm)	2.22 mm
Insulation Color Code	Black with number coding + 1 Yellow/Green (DIN VDE 0293)

Outer Jacket/Sheath Material

Outer Jacket Material	PVC
Nom. Overall Diameter (mm)	11.6 mm

Physical/Mechanical Properties

Temperature Range	-15°C To +70°C (Occasional movement) -40°C To +80°C (Fixed installation)
Oil Resistance	DIN EN 50290-2-22 (TM54)
UV Resistance	Yes
Fire Retardant	DIN EN 60332-1-2
Bending Radius	10 x OD (Occasional movement) 4 x OD (Fixed installation)
Nom. Cable Weight (kg/km)	255

Electrical Properties

Voltage Rating (V)	VDE: 300/500V UL AWM 2464: 300V RMS
Max. Conductor Resistance @20°C	13.3 Ω/km

*Ordering stock code will be created at the time of placing the order and the stock code will include cable part code, outer jacket color & putup length.

© 2015 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.